

ENERGY ADVANTAGE™

MULTI-LOAD RIGID-MOUNT WASHERS

MXR20PN, MXR25PN, MXR30PN, MXR40PN, MXR55PN, MXR65PN

OPL MARKET

Introducing the new Maytag Commercial Laundry Energy Advantage™ Multi-Load Rigid-Mount Washers, the next generation of multi-load washers built for the demands of today and tomorrow.



Faster Spin

- 200 G spin speed extracts more water resulting in faster dry times



Better Energy and Cleaning Performance

- TurboWash™ System spray baffles and tumble patterns provide optimal water savings and cleaning



Easy-to-Use Controls

- 20 preset wash programs
- Multiple language options



USB Programmability

- Easy uploads and downloads of machine settings and software



New Door Design

- Larger door opening and 180-degree door swing allows for easier loading and unloading
- Oversized ergonomic door knob for easy opening
- Durable integrated door hinges



Model MXR40PN shown.



Visit maytagcommerciallaundry.com

WHAT'S INSIDE MATTERS™

MY140244 8/14

ENERGY ADVANTAGE™ MULTI-LOAD RIGID-MOUNT WASHERS

MXR20PN, MXR25PN, MXR30PN, MXR40PN, MXR55PN, MXR65PN

OPL MARKET

WASHER SPECIFICATIONS						
MODEL	MXR20PNATS	MXR25PNATS	MXR30PNATS	MXR40PNATS	MXR55PNATS	MXR65PNATS
MOTOR						
Inverter Drive	Yes	Yes	Yes	Yes	Yes	Yes
Variable Speed	Yes	Yes	Yes	Yes	Yes	Yes
HP (kw)	0.5 (0.4)	0.75 (0.55)	1.0 (0.75)	1.5 (1.1)	2.0 (1.5)	2.0 (1.5)
Voltage	208–240V Single-Phase or Three-Phase	208–240V Single-Phase or Three-Phase	208–240V Single-Phase or Three-Phase	208–240V Single-Phase or Three-Phase	208–240V Single-Phase or Three-Phase	208–240V Single-Phase or Three-Phase
BREAKER SIZE—AMPS	10A	10A	15A	15A	15A	15A
SPIN SPEED						
Extract Speed—Max rpm	820	760	760	690	690	690
Extract Speed—Max g-force	200	200	200	200	200	200
LIQUID SOAP SIGNALS	Yes	Yes	Yes	Yes	Yes	Yes
USB PROGRAMMABILITY	Yes	Yes	Yes	Yes	Yes	Yes
WATER INLET/HOSE						
Water Inlet—in.	BSP 3/4	BSP 3/4	BSP 3/4	BSP 3/4	BSP 3/4	BSP 3/4
Operating Pressure—psi /bar	14.5–116/1–8	14.5–116/1–8	14.5–116/1–8	14.5–116/1–8	14.5–116/1–8	14.5–116/1–8
Drain Size Diameter—in. (mm)	3 (76)	3 (76)	3 (76)	3 (76)	3 (76)	3 (76)
CAPACITY						
Lbs. (kg)	20 (9)	25 (11)	30 (14)	40 (18)	55 (24)	65 (28)
Cylinder Volume—cu. ft. (liters)	2.65 (75)	3.71 (105)	4.77 (135)	6.36 (180)	8.48 (240)	9.89 (280)
Cylinder Diameter—in. (mm)	20.87 (530)	24.4 (620)	24.4 (620)	29.53 (750)	29.53 (750)	29.53 (750)
Cylinder Depth—in. (mm)	13.39 (340)	13.71 (348)	17.63 (448)	16.05 (408)	21.40 (544)	24.95 (634)
COLOR						
Front Panel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Side Panels	Dark Gray	Dark Gray	Dark Gray	Dark Gray	Dark Gray	Dark Gray
APPROXIMATE WEIGHT						
Crated—lbs. (kg)	320 (145)	408 (185)	441 (200)	739 (335)	783 (355)	849 (385)
Uncrated—lbs. (kg)	298 (135)	375 (170)	419 (190)	695 (315)	728 (330)	783 (355)
DIMENSIONS						
Height—in. (mm)	43.89 (1115)	48.22 (1225)	48.22 (1225)	55.51 (1410)	55.51 (1410)	55.51 (1410)
Width—in. (mm)	25.98 (660)	29.53 (750)	29.53 (750)	35.03 (890)	35.03 (890)	35.03 (890)
Depth Including Handle and Vent on Back—in. (mm)	30.91 (785)	30.91 (785)	35.43 (900)	36.02 (915)	41.73 (1060)	44.68 (1135)
Floor to Bottom of Door—in. (mm)	13.74 (349)	13.46 (342)	13.46 (342)	18.31 (465)	18.31 (465)	18.31 (465)
Floor to Drain Outlet Center—in. (mm)	3.46 (88)	3.85 (98)	3.85 (98)	5.12 (130)	5.12 (130)	5.12 (130)
Side to Drain Outlet Center—in. (mm)	6.53 (166)	8.85 (225)	8.85 (225)	11.02 (280)	11.02 (280)	11.02 (280)
Door Opening Diameter—in. (mm)	12.99 (330)	16.14 (410)	16.14 (410)	18.11 (460)	18.11 (460)	18.11 (460)

See specific instructions for proper installation.



Three-Year Limited Warranty on Parts. For the first three (3) years from the date of purchase, when this commercial appliance is installed, maintained and operated according to the instructions attached to or furnished with the product, Maytag Commercial Laundry brand of Whirlpool Corporation (hereafter “Maytag”) will pay for factory-specified parts or original equipment manufacturer parts to correct defects in materials or workmanship.

Fourth- and Fifth-Year Limited Warranty on Certain Parts. In the fourth and fifth years from the date of purchase, Maytag will pay for the following washer parts: the outer shell, drum and shaft assembly, inner welded frame, and bearings and seals. See complete warranty for details.